

INCIDENT RADIO COMMUNICATIONS PLAN			Incident Name SMM COM PLAN - WNQO260			Date/Time Prepared 7/2017		Operational Period Date/Time CONTINUOUS		
Ch #	Function	Channel Name/Trunked Radio System Talkgroup	Assignment	RX Freq N or W	RX Tone/NAC	TX Freq N or W	Tx Tone/NAC	Mode A, D or M	Remarks	
1	SMM-1	GROUP 1	PRIMARY	154.4150 N	127.3	156.1800 N	127.3	M	PRIMARY	
2	SMM-2	GROUP 1	SIMPLEX	154.4150 N	127.3	154.4150 N	127.3	M	LOCAL TACTICAL	
3	SMM-3	GROUP 1	SIMPLEX	154.1300 N	127.3	154.1300 N	127.3	M	LOCAL TACTICAL	
4	VFIRE21	GROUP 1	SIMPLEX	154.2800 N	156.7	154.2800 N	CS	M	INTEROP	
5	VFIRE22	GROUP 1	SIMPLEX	154.2650 N	CS	154.2650 N	CS	M	INTEROP	
6	VFIRE23	GROUP 1	SIMPLEX	154.2950 N	CS	154.2950 N	CS	M	INTEROP	
7										
8										
9										
10										
11										
12										
13										
14										
15										
16										
Prepared by (Communications Unit) Michael S. Williams					Incident Location County Santa Barbara State CA Latitude N Longitude W					

The convention calls for frequency lists to show four digits after the decimal place, followed by either an "N" or a "W", depending on whether the frequency is narrow or wide band. Mode refers to either "A" or "D" indicating analog or digital (e.g. Project 25) or "M" indicating mixed mode. All channels are shown

as if programmed in a control station, mobile or portable radio. Repeater and base stations must be programmed with the Rx and Tx reversed.